

Permit No. _____
Owner: _____
Site Address: _____
Contractor: _____



MOISTURE CONTENT ACKNOWLEDGEMENT

To conform with Section R318.2 of the 2017 Oregon Residential Specialty Code (ORSC), I am notifying the building official that I am aware of the moisture content requirement and have taken steps to meet this code requirement.

Section R318.2 MOISTURE CONTROL

R318.1 Vapor retarders. In all framed walls, floors and roof/ceilings comprising elements of the building thermal envelope, a Class II vapor retarder shall be installed on the warm-in-winter side of the insulation.

Exceptions:

1. In construction where moisture or freezing will not damage the materials.
2. Where the framed cavity or space is ventilated to allow moisture to escape

**This project utilized the following vapor barrier retarder method on the walls
PLEASE CHECK APPROPRIATE BOX BELOW:**

- ☐ Paper faced insulation was utilized on the wall
- ☐ Unfaced insulation with visqueen (polyethylene plastic) applied
- ☐ A vapor block paint/ primer will be applied to the walls

Section R318.2 Moisture content. Prior to the installation of interior finishes, the *building official* shall be notified in writing by the general contractor that all moisture sensitive wood framing members used in construction have a moisture content of not more than 19 percent of the weight of dry wood framing members.

Signature

Date